

DIRECT REPLACEMENT FOR DIAGNETICS LPF639V25 HYDRAULIC FILTER ELEMENT



SPECIFICATIONS:

Weight 14 lbs

Dimensions $39 \times 6 \times 6$ in

O.D. 6.0" **I.D. Bottom** 3.28"

Length Overall 38.59

Construction Type Double Open End, Optimized Microglass

Efficiency 25 Micron; Beta 25 = 1000 per ISO

16889

Gasket Material Viton

Wire Support Yes

Max Operating

Pressure

150 PSID Collapse

Max Temp 250 Degrees F

Weight Each 14

Carton Qty 1

Condition New

This ISO Filtration hydraulic filter element is a direct replacement for the **Diagnetics LPF639V25** hydraulic filter element in form, fit, and function. The optimized filter media provides fine filtration, long life, and high dirt-holding capacity.

- Made in America for assured performance
- Quality ISO 9001:2015 certified manufacturing
- High-performance filter media tested to ISO 16889 protocols

SKU: L2349-62977

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One

N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

