



ISO FILTRATION
QUALITY-SERVICE-VALUE

Source One N.A. LLC - ISO Filtration
701 Green Valley Road
Suite 100-1007
Greensboro, NC 27408

DIRECT REPLACEMENT FOR DONALDSON P165162 HYDRAULIC FILTER ELEMENT



SPECIFICATIONS:

O.D.	3.81"
I.D. Top	1.71"
I.D. Bottom	1.71"
Length Overall	25.58"
Construction Type	Double Open End, Optimized Microglass
Efficiency	6 Micron; Beta 6 = 1000 per ISO 16889
Gasket Material	Viton
Wire Support	Yes
Max Operating Pressure	150 PSID Collapse
Max Temp	250 Degree F
Weight Each	7
Carton Qty	1
Condition	New

This ISO Filtration hydraulic filter element is a direct replacement for the **Donaldson P165162** hydraulic filter element in form, fit, and function. The optimized filter media provides fine filtration, long life, and high dirt-holding capacity.

- Made in **America** for assured performance
- Quality **ISO 9001:2015** certified manufacturing
- High-performance filter media tested to **ISO 16889** protocols

SKU: L3593-63007

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

