



ISO FILTRATION
QUALITY-SERVICE-VALUE

Source One N.A. LLC - ISO Filtration
701 Green Valley Road
Suite 100-1007
Greensboro, NC 27408

DIRECT REPLACEMENT FOR DONALDSON P566251 HYDRAULIC FILTER ELEMENT



SPECIFICATIONS:

O.D.	1.97"
I.D. Top	0.96"
I.D. Bottom	NA
Length Overall	8.15"
Construction Type	Optimized Microglass, Single Open End
Efficiency	10 Micron; B9.9 = 200, B12.4 = 1000 per ISO 16889
Gasket Material	Viton
Wire Support	Yes
Max Operating Pressure	3000 PSID Collapse
Max Temp	250 Degress F
Weight Each	3
Carton Qty	1
Condition	New

High-performance, direct replacement for **Donaldson P566251** hydraulic filter element in form, fit, and function. **Made in America** with ISO 9001:2015 compliant manufacturing for assured quality. Optimized media **tested to ISO 16889** is used for fine filtration, long life, and high dirt-holding capacity.

- 1.97" OD x 0.96" ID Top x 8.15" Length overall
- **10 Micron**; B9.9 = 200, B12.4 = 1000 per ISO 16889
 - 3000 PSID Collapse Pressure

SKU: L8887-58520

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

