



ISO FILTRATION
QUALITY-SERVICE-VALUE

Source One N.A. LLC - ISO Filtration
701 Green Valley Road
Suite 100-1007
Greensboro, NC 27408

DIRECT REPLACEMENT FOR FAI FILTRI 5740545 HYDRAULIC FILTER ELEMENT



SPECIFICATIONS:

O.D.	2.76"
I.D. Top	1.61"
I.D. Bottom	29 PSID Bypass Valve
Length Overall	11.96"
Construction Type	29 PSID Bypass Valve, Optimized Microglass
Efficiency	10 Micron; B9.9 = 200, B12.4 = 1000 per ISO 16889
Gasket Material	Viton
Wire Support	Yes
Max Operating Pressure	232 PSID Collapse
Max Temp	250 Degrees F
Weight Each	2.5
Carton Qty	1
Condition	New

High-performance, direct replacement for **Fai Filtri 5740545** hydraulic filter element in form, fit, and function. **Made in America** with ISO 9001:2015 compliant manufacturing for assured quality. Optimized microglass media **tested to ISO 16889** is used for fine filtration, long life, and high dirt-holding capacity.

- 2.76" OD x 1.61" ID Top x 11.96" Length overall
- **10 Micron**; B9.9 = 200, B12.4 = 1000 per ISO 16889
 - 232 PSID Collapse
- Scroll down for additional specs

SKU: L2932-430490

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

