



ISO FILTRATION
QUALITY-SERVICE-VALUE

Source One N.A. LLC - ISO Filtration
701 Green Valley Road
Suite 100-1007
Greensboro, NC 27408

FILTERMART 01-0196 DIRECT REPLACEMENT FILTER ELEMENT



SPECIFICATIONS:

O.D.	6.0"
I.D. Top	2.62"
I.D. Bottom	2.62"
Length Overall	18.0"
Construction Type	Double Open-End, Optimized cellulose
Efficiency	10 Micron
Gasket Material	Buna
Protective Jacket	Yes
Max Operating Pressure	100 PSID Collapse Pressure
Max Temp	248 Degrees F
Weight Each	5
Carton Qty	6
Condition	New

High-performance, **Guaranteed** direct replacement for **Filtermart 01-0196** High-Flow filter element in form, fit, and function. **Made in America** for assured quality. Optimized media **tested to ISO 16889** is used for excellent filtration, long life, and high dirt-holding capacity.

- 6.0" OD x 2.62" ID Top x 18.0" Length overall
 - **10 Micron** efficiency rating
- Optimized cellulose, Double Open-End

SKU: IHF389-61826210

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

