

DIRECT REPLACEMENT FOR FLUITEK FLK02-07780 HYDRAULIC FILTER ELEMENT



SPECIFICATIONS:

O.D.	2.10"
I.D. Top	0.97"
I.D. Bottom	0.97"
Length Overall	4.72"
Construction Type	Double Open End, Optimized Microglass
Efficiency	3 Micron; B3 = 1000 per ISO 16889
Gasket Material	Viton
Wire Support	Yes
Max Operating Pressure	300 PSID Collapse
Max Temp	250 Degree F
Weight Each	1
Carton Qty	1
Condition	New

High-performance, direct replacement for **Fluitek FLK02-07780** hydraulic filter element in form, fit, and function. **Made in America** with ISO 9001:2015 compliant manufacturing for assured quality. Optimized microglass media **tested to ISO 16889** is used for fine filtration, long life, and high dirt-holding capacity.

- 2.10" OD x 0.97" ID Top x 4.72" Length overall
 - **3 Micron**; B3 = 1000 per ISO 16889
 - 300 PSID Collapse

SKU: L3972-63015

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

