

DIRECT REPLACEMENT FOR FLUITEK FLK02-13830 HYDRAULIC FILTER ELEMENT



SPECIFICATIONS:

O.D. 4.96"

I.D. Top 3.62"

I.D. Bottom Bolt Hole

Length Overall 15.4"

Construction Type Optimized Microglass, Single Open End with bolt hole; inside-to-outside flow 3 Micron; B3 = 200, B4.5 = 1000 per ISO

Efficiency 16889

Gasket Material Viton
Wire Support Yes

Ann On anathra

Max Operating Pressure

150 PSID Collapse

Max Temp 230 Degress F

Weight Each 4

Carton Qty 1

Condition New

This ISO Filtration hydraulic filter element is a direct replacement for the **Fluitek FLK02-13830** hydraulic filter element in form, fit, and function. The optimized filter media provides fine filtration, long life, and high dirt-holding capacity.

• Made in America for assured performance

• Quality ISO 9001:2015 certified manufacturing

• High-performance filter media tested to **ISO 16889** protocols

SKU: L5685-63633

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One

N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

