

## FLUITEK P6018-10W2 DIRECT REPLACEMENT FILTER ELEMENT



### SPECIFICATIONS:

|                        |                                      |
|------------------------|--------------------------------------|
| O.D.                   | 6.0"                                 |
| I.D. Top               | 2.62"                                |
| I.D. Bottom            | 2.62"                                |
| Length Overall         | 18.0"                                |
| Construction Type      | Double Open-End, Optimized cellulose |
| Efficiency             | 10 Micron                            |
| Gasket Material        | Buna                                 |
| Protective Jacket      | Yes                                  |
| Max Operating Pressure | 100 PSID Collapse Pressure           |
| Max Temp               | 248 Degrees F                        |
| Weight Each            | 5                                    |
| Carton Qty             | 6                                    |
| Condition              | New                                  |

High-performance, **Guaranteed** direct replacement for **Fluitek P6018-10W2** High-Flow filter element in form, fit, and function. **Made in America** for assured quality. Optimized media **tested to ISO 16889** is used for excellent filtration, long life, and high dirt-holding capacity.

- 6.0" OD x 2.62" ID Top x 18.0" Length overall
  - **10 Micron** efficiency rating
- Optimized cellulose, Double Open-End

---

SKU: IHF349-61826210

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

