

## HILCO PL718 DIRECT REPLACEMENT FILTER ELEMENT



## **SPECIFICATIONS:**

Weight 5 lbs

**Dimensions**  $18 \times 6 \times 6$  in

**O.D.** 6.0"

**I.D. Top** 2.62"

**I.D. Bottom** 2.62"

Length Overall 18.0"

Construction Type Double Open-End, Optimized cellulose

Efficiency 20 Micron

Gasket Material Buna

**Protective Jacket** Yes

**Max Operating** 

Pressure

100 PSID Collapse Pressure

Max Temp 248 Degrees F

Weight Each 5

Carton Qty 6

Condition New

High-performance, **Guaranteed** direct replacement for **Hilco PL718** High-Flow filter element in form, fit, and function. **Made in America** for assured quality. Optimized media **tested to ISO 16889** is used for excellent filtration, long life, and high dirt-holding capacity.

- 6.0" OD x 2.62" ID Top x 18.0" Length overall
  - 20 Micron efficiency rating
  - Optimized cellulose, Double Open-End

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One

N.A. is authorized or licensed to makketile 5588591826230 hanufacturer's name or trademark.

