



**DIRECT REPLACEMENT FOR PALL HC6400FKP13Z HYDRAULIC FILTER ELEMENT**



**SPECIFICATIONS:**

<b>O.D.</b>	3.42"
<b>I.D. Top</b>	1.96"
<b>I.D. Bottom</b>	NA
<b>Length Overall</b>	12.88"
<b>Construction Type</b>	Optimized Microglass, Single Open End
<b>Efficiency</b>	3 Micron; B3 = 200, B4.5 = 1000 per ISO 16889
<b>Gasket Material</b>	Viton
<b>Wire Support</b>	Yes
<b>Max Operating Pressure</b>	150 PSID Collapse
<b>Max Temp</b>	250 Degrass F
<b>Weight Each</b>	2.5
<b>Carton Qty</b>	1
<b>Condition</b>	New

High-performance, direct replacement for **Pall HC6400FKP13Z** hydraulic filter element in form, fit, and function. **Made in America** with ISO 9001:2015 compliant manufacturing for assured quality. Optimized media **tested to ISO 16889** is used for fine filtration, long life, and high dirt-holding capacity.

- 3.42" OD x 1.96" ID Top x 12.88" Length overall
- **3 Micron**; B3 = 200, B4.5 = 1000 per ISO 16889
  - 150 PSID Collapse Pressure

---

**SKU: L8272-62826**

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

