

## **DIRECT REPLACEMENT FOR PARKER 933777 HYDRAULIC FILTER ELEMENT**



## **SPECIFICATIONS:**

O.D. 6.0"

I.D. Top 3.28"

I.D. Bottom 3.28"

Length Overall 16.82"

Construction Type Double Open End, Optimized Microglass

**Efficiency** 10 Micron; B9.9 = 200, B12.4 = 1000 per

ISO 16889

Gasket Material Viton
Wire Support Yes

Wire Support Ye

Max Operating

Pressure

150 PSID Collapse

Max Temp 250 Degrees F

Weight Each 3.5
Carton Qty 1

Condition New

This ISO Filtration hydraulic filter element is a direct replacement for the **Parker 933777** hydraulic filter element in form, fit, and function. The optimized filter media provides fine filtration, long life, and high dirt-holding capacity.

• Made in **America** for assured performance

• Quality ISO 9001:2015 certified manufacturing

• High-performance filter media tested to ISO 16889 protocols

SKU: L1370-62947

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One

N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

