

## DIRECT REPLACEMENT FOR PARKER FC1098Q005BS HYDRAULIC FILTER ELEMENT



## **SPECIFICATIONS:**

O.D. 4.96"
 I.D. Top 3.62"
 I.D. Bottom Bolt Hole
 Length Overall 15.4"

Construction Type Optimized Microglass, Single Open End with bolt hole; inside-to-outside flow

Efficiency 5 Micron; B5 = 200, B7.7 = 1000 per ISO 16889

Yes

Gasket Material Viton

Max Operating

Wire Support

Pressure .

150 PSID Collapse

Max Temp 230 Degress F

Weight Each 4

Carton Qty 1

Condition New

This ISO Filtration hydraulic filter element is a direct replacement for the **Parker FC1098Q005BS** hydraulic filter element in form, fit, and function. The optimized filter media provides fine filtration, long life, and high dirt-holding capacity.

- Made in America for assured performance
- Quality ISO 9001:2015 certified manufacturing
- High-performance filter media tested to **ISO 16889** protocols

SKU: L5705-63635

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One

N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

