

## DIRECT REPLACEMENT FOR PARKER FC1372Q005BS HYDRAULIC FILTER ELEMENT



### SPECIFICATIONS:

|                               |                                               |
|-------------------------------|-----------------------------------------------|
| <b>O.D.</b>                   | 3.81"                                         |
| <b>I.D. Top</b>               | 1.71"                                         |
| <b>I.D. Bottom</b>            | 1.71"                                         |
| <b>Length Overall</b>         | 12.87"                                        |
| <b>Construction Type</b>      | Double Open End, Optimized Microglass         |
| <b>Efficiency</b>             | 5 Micron; B5 = 200, B7.7 = 1000 per ISO 16889 |
| <b>Gasket Material</b>        | Viton                                         |
| <b>Wire Support</b>           | Yes                                           |
| <b>Max Operating Pressure</b> | 150 PSID Collapse                             |
| <b>Max Temp</b>               | 248 Degrees F                                 |
| <b>Weight Each</b>            | 5                                             |
| <b>Carton Qty</b>             | 1                                             |
| <b>Condition</b>              | New                                           |

This ISO Filtration hydraulic filter element is a direct replacement for the **Parker FC1372Q005BS** hydraulic filter element in form, fit, and function. The optimized filter media provides fine filtration, long life, and high dirt-holding capacity.

- Made in **America**
- **ISO 9001:2015** certified manufacturing
- Filter media tested to **ISO 16889** protocols

---

**SKU:** L3155-62997

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

