



DIRECT REPLACEMENT FOR PARKER G02815 HYDRAULIC FILTER ELEMENT



SPECIFICATIONS:

| | |
|-------------------------------|---------------------------------------|
| O.D. | 6.0" |
| I.D. Top | 3.29" |
| I.D. Bottom | 3.29" |
| Length Overall | 8.25" |
| Construction Type | Double Open End, Optimized Microglass |
| Efficiency | 3 Micron; B3 = 200, B4.5 = 1000 |
| Gasket Material | Viton |
| Wire Support | Yes |
| Max Operating Pressure | 150 PSID |
| Max Temp | 250 Degrees F |
| Weight Each | 3.5 |
| Carton Qty | 1 |
| Condition | New |

This ISO Filtration hydraulic filter element is a direct replacement for the **Parker G02815** hydraulic filter element in form, fit, and function. The optimized filter media provides fine filtration, long life, and high dirt-holding capacity.

- Made in **America** for assured performance
- Quality **ISO 9001:2015** certified manufacturing
- High-performance filter media tested to **ISO 16889** protocols

SKU: L995-62935

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

