

REPLACEMENT FOR CATERPILLAR 9U6984 SPIN-ON FILTER



SPECIFICATIONS:

Weight	4.5 lbs
Dimensions	12 × 6 × 6 in
O.D.	5.06"
I.D. Top	1-1/2" UNF
I.D. Bottom	NA
Length Overall	10.94"
Construction Type	Optimized Microglass Media in a plain white spin-on filter
Efficiency	10 Micron; B9.9 = 200, B12.4 = 1000 per ISO 16889
Gasket Material	Buna
Max Flow	40 GPM
Burst/Core Collapse Pressure	261 PSI Burst/145 PSID Collapse
Max Temp	248 Degrees F
Weight Each	4.5
Carton Qty	6
Condition	New

This ISO Filtration spin-on filter is a direct replacement for the **Caterpillar 9U6984** spin-on filter in form, fit, and function. The optimized filter media provides fine filtration, long life, and high dirt-holding capacity.

- Made in **America** for assured performance
- Quality **ISO 9001:2015** certified manufacturing
- High-performance filter media tested to **ISO 16889** protocols

SKU: SP293-075

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

