

DIRECT REPLACEMENT FOR REXROTH 168700RH3XLS000M HYDRAULIC FILTER ELEMENT



SPECIFICATIONS:

Weight 1 lbs

Dimensions $5 \times 3 \times 3$ in

O.D. 2.10"

I.D. Top 0.97"

I.D. Bottom 0.97"

Length Overall 4.72"

Construction Type Double Open End, Optimized Microglass

Efficiency 3 Micron; B3 = 200, B4.5 = 1000 per ISO

16889

Gasket Material Viton

Wire Support Yes

Max Operating

Pressure

300 PSID Collapse

Max Temp 250 Degress F

Weight Each 1

Carton Qty 1

Condition New

This ISO Filtration hydraulic filter element is a direct replacement for the **Rexroth 168700RH3XLS000M** hydraulic filter element in form, fit, and function. The optimized filter media provides fine filtration, long life, and high dirt-holding capacity.

- Made in America for assured performance
- Quality ISO 9001:2015 certified manufacturing
- High-performance filter media tested to ISO 16889 protocols

SKU: L4037-63015

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One

N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

