

DIRECT REPLACEMENT FOR SEPARATION TECHNOLOGIES 3902GGMB04 HYDRAULIC FILTER ELEMENT



SPECIFICATIONS:

O.D.	1.76"
I.D. Top	0.98"
I.D. Bottom	NA
Length Overall	4.45"
Construction Type	Optimized Microglass, Single Open End
Efficiency	20 Micron; B20 = 200, B26.6 = 1000 per ISO 16889
Gasket Material	Viton
Wire Support	Yes
Max Operating Pressure	350 PSID Collapse
Max Temp	250 Degress F
Weight Each	2
Carton Qty	1
Condition	New

This ISO Filtration hydraulic filter element is a direct replacement for the **Separation Technologies 3902GGMB04** hydraulic filter element in form, fit, and function. The optimized filter media provides fine filtration, long life, and high dirt-holding capacity.

- Made in **America** for assured performance
- Quality **ISO 9001:2015** certified manufacturing
- High-performance filter media tested to **ISO 16889** protocols

SKU: L5376-58400

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

