



DIRECT REPLACEMENT FOR SOFIMA 48151 HYDRAULIC FILTER ELEMENT



SPECIFICATIONS:

| | |
|-------------------------------|---|
| O.D. | 2.05" |
| I.D. Top | 0.97" |
| I.D. Bottom | 24.7 PSID Bypass Valve |
| Length Overall | 2.95" |
| Construction Type | 24.7 PSID Bypass Valve, Cellulose Media |
| Efficiency | 20 Micron |
| Gasket Material | Viton |
| Wire Support | NA |
| Max Operating Pressure | 44 PSID Collapse |
| Max Temp | 248 Degrees F |
| Weight Each | 1.25 |
| Carton Qty | 1 |
| Condition | New |

High-performance, direct replacement for **Sofima 48151** hydraulic filter element in form, fit, and function. **Made in America** with ISO 9001:2015 compliant manufacturing for assured quality. Optimized media **tested to ISO 16889** is used for fine filtration, long life, and high dirt-holding capacity.

- 2.05" OD x 0.97" ID Top x 2.95" Length overall
 - **20 Micron**
 - 44 PSID Collapse

SKU: W5057-62259

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

