

## **DIRECT REPLACEMENT FOR SWIFT SF8300-39-12UM HYDRAULIC FILTER ELEMENT**



## **SPECIFICATIONS:**

Weight 19 lbs

**Dimensions**  $40 \times 6 \times 6$  in

O.D. 5.97"
I.D. Top 4.13"
I.D. Bottom 4.13"

Length Overall 38.4"

Construction Type Double Open End, Optimized Microglass

Efficiency 10 Micron; B9.9 = 200, B12.4 = 1000 per

y ISO 16889

Gasket Material Viton

Wire Support Yes

**Max Operating** 

Pressure

160 PSID Collapse

Max Temp 230 Degress F

Weight Each 18
Carton Qty 1

Condition New

This ISO Filtration hydraulic filter element is a direct replacement for the **Swift SF8300-39-12UM** hydraulic filter element in form, fit, and function. The optimized filter media provides fine filtration, long life, and high dirt-holding capacity.

- Made in America
- ISO 9001:2015 certified manufacturing
- Filter media tested to ISO 16889 protocols

**SKU:** L5656-62913

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One

N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

