

## **DIRECT REPLACEMENT FOR ZINGA S0810HN HYDRAULIC FILTER ELEMENT**



## **SPECIFICATIONS:**

O.D. 1.97"

I.D. Top 0.96"

I.D. Bottom NA

Length Overall 8.15"

Construction Type Optimized Microglass, Single Open End

20 Micron; B20 = 200, B26.6 = 1000 per

ISO 16889

Gasket Material Viton
Wire Support Yes

**Max Operating** 

Pressure 3000 PSID Collapse

Max Temp 250 Degress F

Weight Each 3
Carton Qty 1

Condition New

High-performance, direct replacement for **Zinga S0810HN** hydraulic filter element in form, fit, and function. **Made in America** with ISO 9001:2015 compliant manufacturing for assured quality. Optimized media **tested to ISO 16889** is used for fine filtration, long life, and high dirt-holding capacity.

• 1.97" OD x 0.96" ID Top x 8.15" Length overall

• **20 Micron**; B20 = 200, B26.6 = 1000 per ISO 16889

• 3000 PSID Collapse Pressure

SKU: L9253-58524

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One

N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

